



Installation:

Shutter can be installed as either a fixed or operable panel. Shutter must be installed in accordance to mounting instructions. If nailing or screwing through the face of the shutter, screw or nail head must be filled and painted over to keep water from penetrating material. Hardware kit is available for a nominal charge.

Material:

Extira™ Exterior Wood Composite.

Finish Options:

Primed - Insl-x Corotech Oil Base

Painted - Nine Standard colors (Page 10) or unlimited custom colors. Set up charge required for all custom colors.

Hardware:

A complete line of standard and functioning hardware is available. See pages 10-13

Warranty:

We warrant all our products to be free of manufacturers defects for the life of the shutter. Extira™ Composite is additionally warranted for ten years. Paint coat carries the paint manufacturers warranty. We use Benjamin Moore and PPG paints exclusively. The warranties are available at www.benjaminmoore.com.

Specifications

- Thickness.....1.25"
- Top Rail.....2.5"
- Center Rail.....2.5" (2.125 on louver.)
- Bottom Rail.....Varies (2.5" on panels.)
- Stile Width.....2.5"
- Louver.....1" Closed
- Panel Thickness......625"

Widths Available

10"-30" in 1/4" increments
(custom widths are an option,. Widths under 11" require a 1.5" stile. Call for availability)

Lengths Available

26" - 96" in 1/4" increments
(custom lengths are an option,. Call for availability)

